


NEW

# SoilWave™

- 5/8" continuous wave height design. As blade wears, the wave height and soil action do not change, and the blade maintains its aggressive action
- Made from proprietary boron alloy steel
- Design allows for easier soil penetration in tough conditions
- Suitable for mounting on no-till and minimum tillage planting, seeding and fertilizer equipment — and for vertical tillage machines



Slotted holes to fit 5" and 5.25"  
BOLT CIRCLE HUBS 4" center hole

16" x 4.5mm	8.8 lbs	75 per bolt	slotted cluster hole pattern
17" x 5mm	11.03 lbs	75 per bolt	slotted cluster hole pattern only
18" x 5mm	13.1 lbs	75 per bolt	slotted cluster hole only
20" x 5mm	17.27 lbs	75 per bolt	slotted cluster hole and single 1.75" shaft size hole
20" x 6.5mm	22.4 lbs	60 per bolt	1.75" shaft center hole only
22" x 5mm	21.5 lbs	60 per bolt	slotted hole cluster and single 1.75" shaft size hole
22" x 6.5mm	27.5 lbs	50 per bolt	1.75" shaft hole only



Ingersoll Tillage Group

ISO 9001:2008 Certified  
(888) 768-1740 [www.IngersollTillage.com](http://www.IngersollTillage.com)

Innovative, effective products for tillage and planting worldwide.